

Multipurpose Lithium 3 Grease

Product description

A premium quality lithium based multipurpose grease manufactured from superior quality base stocks with specially selected additives having high drop point, good thermal stability, resistance to oxidation and structural stability. This provide protection against rust, corrosion and water wash out.

Applications

For the lubrication of plain roller bearings, guide ways, machine parts etc.

Advantages

Good thermal stability • Protects against rust and corrosion • Service temperature -10°C to +130°C .

Handling instructions

The grease is to be applied by brush, or grease gun. Fill only required quantity. Refer MSDS for more information about safe use, physical & health hazards.

Technical Properties

Parameter	Value	Unit	Standard
Appearance	Smooth grease		
Base	Mineral oil, Lithium soap		
Colour#	Brown		
Penetration	265 - 295	mm/10	ASTM D 217
Drop point	>180	°C	ASTM D 566
Four Ball Load, min	200	kg	ASTM D 2596
Service temperature	- 10 to +130	°C	

Minor colour variation is possible but product quality will remain same

Limited warranty: The information & data contained in this catalogue is accurate to the best of our knowledge or is obtained from sources, tests or experience believed by us to be accurate. User is responsible for determining whether this is fit for a particular application. We make no representation of any kind & data mentioned herein is offered without any warranty. TriboCor's sole warranty is that the product will meet the specs at the time of shipment. All data is subject of change without prior notice.

V1120

TriboCor Technologies Private Limited,

57/3, Opp NKCA Pharmacy, Srirampura, Mysore - 570008, India.
Customer Care : 0821 2361110, +91 934 258 9006, +91 984 409 2722
E-mail : tribocor@gmail.com Web : www.tribocor.co.in

TriboCor[®]
High Performance Aerosol