White Assembly Paste TC 12



Product description

White Assembly Paste TC 12 is a non-staining assembly lubricant used for the application in food industry, plastic, printing and textile machinery where dark coloured lubricants cannot be used.

Applications

For assembly, lubrication of machinery and equipment's in textile, printing, plastic industries. It also prevents fretting corrosion.

Advantages

Excellent shear and mechanical stability • Resistant to ageing • Good resistant to water & other chemicals • Good high and low temperature performance • Service temperature -20°C to +150°C

Handling instructions

The paste is to be applied by brush, or grease gun. Fill only required quantity. Refer MSDS for more information about safe use, physical & health hazards.

Technical Properties

Parameter	Value	Unit	Standard
Appearance	Smooth paste		
Base	Mineral & solid lubricants		
Thickener	Lithium		
Colour#	Off-white		
Penetration	265 - 295	mm/10	ASTM D 217
Drop point	> 165	°C	ASTM D 566
Service temperature	- 20 to + 150	°C	

[#] Minor colour variation is possible but product quality will remain same

Limited warranty: The information & data contained in this catalogue is accurate to the best of our knowledge or is obtained from sources, tests or experience believed by us to be accurate. User is responsible for determining whether this is fit for a particular application. We make no representation of any kind & data mentioned herein is offered without any warranty. TriboCor's sole warranty is that the product will meet the specs at the time of shipment. All data is subject of change without prior notice.

V1120

E-mail: tribocor@gmail.com Web: www.tribocor.co.in

