

# Silicone Valve & Packing Grease TC 18



## Product description

TC 18 is a thin non-curing silicone grease designed for sealing, lubricating and waterproofing O-rings and other rubber and plastic parts. It insulates valves, electrical contacts, spark plugs, battery terminals and fasteners from moisture and protects against corrosion.

## Applications

For the lubrication of stop cocks and valves in hot and cold water lines. Lubrication of O rings, rubber and plastic seals and components.

## Advantages

Seals, lubricates, protects & insulates • Temperature resistant • Safe on most plastics and rubber • Service temperature -40°C to +200°C • Odourless, tasteless and non-corrosive in nature • Di electric strength 500 v/mil

## Handling instructions

The grease is to be applied by brush, or grease gun. Fill only required quantity. Refer MSDS for more information about safe use, physical & health hazards.

## Technical Properties

Parameter	Value	Unit	Standard
Appearance	Smooth grease		
Base	Silicone oil & inorganic filler		
Colour#	Water white		
Penetration	265 - 295	mm/10	ASTM D 217
Drop point	>240	°C	ASTM D 566
Service temperature	- 40 to + 200	°C	

# Minor colour variation is possible but product quality will remain same

Limited warranty: The information & data contained in this catalogue is accurate to the best of our knowledge or is obtained from sources, tests or experience believed by us to be accurate. User is responsible for determining whether this is fit for a particular application. We make no representation of any kind & data mentioned herein is offered without any warranty.

TriboCor's sole warranty is that the product will meet the specs at the time of shipment. All data is subject of change without prior notice.

V1120

**TriboCor Technologies Private Limited,**

57/3, Opp NKCA Pharmacy, Srirampura, Mysore - 570008, India.  
Customer Care : 0821 2361110, +91 934 258 9006, +91 984 409 2722  
E-mail : tribocor@gmail.com Web : www.tribocor.co.in

**TriboCor**<sup>®</sup>  
*High Performance Aerosol*