

Multipurpose PTFE HT Grease TC 19

Product description

Multipurpose PTFE HT grease TC 19 is based on Aluminium complex soap, special additives and PTFE and designed especially for multifunctional heavy duty and high temperature applications. This grease offers optimum shear stability, uniform adhesion and good load bearing capacity. This grease gives good protection against rust and oxidation.

Applications

It can be used for all types of industrial and automotive bearings subjected to heavy loads & high temperatures applications.

Advantages

Film strength and durability • Withstands extreme pressure and heavy loads • Good corrosion protection • Service temperature -10°C to +230°C

Handling instructions

The grease is to be applied by brush, or grease gun. Fill only required quantity. Refer MSDS for more information about safe use, physical & health hazards.

Technical Properties

Parameter	Value	Unit	Standard
Appearance	Smooth paste		
Base	Mineral oil, PTFE & other solid lubricants		
Colour#	Green		
Penetration	265 - 295	mm/10	ASTM D 217
Drop point	>240	°C	ASTM D 566
Service temperature	- 20 to + 230	°C	

Minor colour variation is possible but product quality will remain same

Limited warranty: The information & data contained in this catalogue is accurate to the best of our knowledge or is obtained from sources, tests or experience believed by us to be accurate. User is responsible for determining whether this is fit for a particular application. We make no representation of any kind & data mentioned herein is offered without any warranty. TriboCor's sole warranty is that the product will meet the specs at the time of shipment. All data is subject of change without prior notice.

V1120

TriboCor Technologies Private Limited,

57/3, Opp NKCA Pharmacy, Srirampura, Mysore - 570008, India.
Customer Care : 0821 2361110, +91 934 258 9006, +91 984 409 2722
E-mail : tribocor@gmail.com Web : www.tribocor.co.in

TriboCor[®]
High Performance Aerosol