

Open Gear & Wire Rope Spray TC 204

Product description

Open Gear & Wire Rope Spray TC 204 is an effective adhesive heavy duty lubricant for lubrication and corrosion protection of open gears, wire ropes, cables, pulleys, gear drives etc.

Applications

Open Gear & Wire Rope Spray TC 204 is used for the lubrication of wide range of open gears, wire ropes and chains.

Advantages

Adhesive lubricant for industrial applications with good penetration properties • Fortified with high load carrying additives. • Good thermal & oxidation stability • It forms highly tenacious film on metal parts and gives excellent performance under hostile conditions

Handling instructions.

Shake the can well till movement of steel ball is audible. Keep away from open flame & heat. Do not store above 50°C .Contents under pressure. Highly flammable material. Check for compatibility before use. Refer MSDS for more information about safe use, physical & health hazards.

Technical Properties

Parameter	Value	Unit	Standard
Appearance	Black oil		
Density	0.90	g/cc	
Viscosity @ 40°C	~ 200	cSt	ASTM D 445
Flash point	< 0	°C	ASTM D 566

Limited warranty: The information & data contained in this catalogue is accurate to the best of our knowledge or is obtained from sources, tests or experience believed by us to be accurate. User is responsible for determining whether this is fit for a particular application. We make no representation of any kind & data mentioned herein is offered without any warranty. TriboCor's sole warranty is that the product will meet the specs at the time of shipment. All data is subject of change without prior notice.

V1120

TriboCor Technologies Private Limited,

57/3, Opp NKCA Pharmacy, Srirampura, Mysore - 570008, India.
Customer Care : 0821 2361110, +91 934 258 9006, +91 984 409 2722
E-mail : tribocor@gmail.com Web : www.tribocor.co.in

TriboCor[®]
High Performance Aerosol