# **Plastic & Rubber Care Spray TC 209**



# **Product description**

Plastic & Rubber Care Spray TC 209 is synthetic oils based product for protecting & renovating plastics & rubbers. Imparts a high gloss finish to plastic components & prevents embrittlement. Works as lubricant & eliminates rattling sound and squeaking noises. It forms very thin 2m, which is non-staining, non-sticky and non-toxic. It can be used as general lubricant.

## **Applications**

Protects, maintains, lubricates & insulates plastic & rubber components.

#### **Advantages**

Colourless non sticky oil • Repels moisture. • High gloss finish

## Handling instructions.

Shake the can well. Keep away from open flame & heat. Do not store above 50°C .Contents under pressure. Highly flammable material. Check for compatibility before use. Refer MSDS for more information about safe use, physical & health hazards.

### **Technical Properties**

Parameter	Value	Unit	Standard	
Appearance	Colourless oil			
Density	0.95	g/cc		
Viscosity @ 25°C	350	cSt	ASTM D 445	
Flash point	< 0	°C	ASTM D 566	

Limited warranty: The information & data contained in this catalogue is accurate to the best of our knowledge or is obtained from sources, tests or experience believed by us to be accurate. User is responsible for determining whether this is fit for a particular application. We make no representation of any kind & data mentioned herein is offered without any warranty. TriboCor's sole warranty is that the product will meet the specs at the time of shipment. All data is subject of change without prior notice.

