Chain Lube Spray Dry TC 212

Product description

TC 212 is a dry chain lubricant for the lubrication and corrosion protection of motor cycle chains. This product is based on fully synthetic base fluids, PTFE, extreme pressure additives, combing excellent anti wear protection & extreme pressure for long life of chain and sprocket.

Applications

Chain Lube Spray Dry Type TC 212 is used for superior lubrication of all types of automobile chains, especially of higher end and race bikes.

Advantages

With outstanding creep and lubricating effect due to presence of PTFE • Particularly suitable for fast-running chains •Reduces chain elongation and helps to extend chain service life. • Extremely adherent and waterproof chain lubricant • Compatible with O,X,Z rings

Handling instructions.

Shake the can well till movement of steel ball is audible. Keep away from open flame & heat. Do not store above 50°C .Contents under pressure. Highly flammable material. Check for compatibility before use. Refer MSDS for more information about safe use, physical & health hazards.

Technical Properties

Parameter	Value	Unit	Standard
Appearance	White fluid		
Density	~ 0.80	g/cc	
Flash point	< 0	°C	ASTM D 566

Limited warranty: The information & data contained in this catalogue is accurate to the best of our knowledge or is obtained from sources, tests or experience believed by us to be accurate. User is responsible for determining whether this is fit for a particular application. We make no representation of any kind & data mentioned herein is offered without any warranty. TriboCor's sole warranty is that the product will meet the specs at the time of shipment. All data is subject of change without prior notice.

TriboCor Technologies Private Limited,

57/3, Opp NKCA Pharmacy, Srirampura, Mysore - 570008, India. Customer Care : 0821 2361110, +91 934 258 9006, +91 984 409 2722 E-mail : tribocor@gmail.com Web : www.tribocor.co.in

