

Mould Release Spray TC 41

Product description

Mould Release Spray TC 41 is silicone based mould release agent. It acts very efficiently as a high release agent on rubber and plastic moulds. It forms very thin film, which is non-staining, non-sticky and non-toxic. It can be used as general lubricant and anti-spatter spray.

Applications

Mould Release Spray TC 41 is used as mould release agent in injection moulding, anti-spatter agent and general lubricant.

Advantages

Forms an even film • Excellent mould separation • Safe on metals • Can be used as general lubricant

Handling instructions.

Shake the can well. Keep away from open flame & heat. Do not store above 50°C .Contents under pressure. Highly flammable material. Check for compatibility before use. Refer MSDS for more information about safe use, physical & health hazards.

Technical Properties

Parameter	Value	Unit	Standard
Appearance	Colourless film		
Density	0.95	g/cc	
Base	Silicone oil		
Viscosity @ 25°C	350	cSt	ASTM D 455
Flash point	< 0	°C	ASTM D 566

Limited warranty: The information & data contained in this catalogue is accurate to the best of our knowledge or is obtained from sources, tests or experience believed by us to be accurate. User is responsible for determining whether this is fit for a particular application. We make no representation of any kind & data mentioned herein is offered without any warranty. TriboCor's sole warranty is that the product will meet the specs at the time of shipment. All data is subject of change without prior notice.

V1120

TriboCor Technologies Private Limited,

57/3, Opp NKCA Pharmacy, Srirampura, Mysore - 570008, India.
Customer Care : 0821 2361110, +91 934 258 9006, +91 984 409 2722
E-mail : tribocor@gmail.com Web : www.tribocor.co.in

TriboCor[®]
High Performance Aerosol