Non Silicone Mould Release Spray TC 43



Product description

Non Silicone Mould Release Spray TC 43 is non-silicone free mould release agent. It acts very efficiently as a high release agent on rubber and plastic moulds. It forms very thin film, which is non-staining, non-sticky and non-toxic. It can be used as general lubricant. This allows easy painting and printing on plastic components and parts.

Applications

Non Silicone Mould Release Spray TC 43 is used as mould release agent in injection moulding, anti-spatter agent and general lubricant.

Advantages

Forms an even film • Excellent mould separation • Safe on metals • Can be used as general lubricant • Bio degradable

Handling instructions.

Shake the can well. Keep away from open flame & heat. Do not store above 50°C .Contents under pressure. Highly flammable material. Check for compatibility before use. Refer MSDS for more information about safe use, physical & health hazards.

Technical Properties

Parameter	Value	Unit	Standard	
Appearance	Colourless film			
Density	~ 0.93	g/cc		
Base	Non silicone base			
Flash point	< 0	°C	ASTM D 566	

Limited warranty: The information & data contained in this catalogue is accurate to the best of our knowledge or is obtained from sources, tests or experience believed by us to be accurate. User is responsible for determining whether this is fit for a particular application. We make no representation of any kind & data mentioned herein is offered without any warranty. TriboCor's sole warranty is that the product will meet the specs at the time of shipment. All data is subject of change without prior notice.

V1120

E-mail: tribocor@gmail.com Web: www.tribocor.co.in

