

# Anti-Spatter Spray TC 44



## Product description

Anti-Spatter Spray TC 44 is based on superior quality silicone oils which are used as welding aid and suitable for all kinds of welding jobs. The spray forms thin a film on the metal surface and prevent metal spatters from sticking.

## Applications

Anti-Spatter Spray TC 44 can be used as release agent on all surfaces. It makes welding easier by eliminating spatter cleaning problem. It can be used for MIG/TIG welding applications

## Advantages

- Even spreading
- It dramatically reduces time spent scrapping, sanding & chipping during clean up

## Handling instructions.

Shake the can well. Keep away from open flame & heat. Do not store above 50°C .Contents under pressure. Highly flammable material. Check for compatibility before use. Refer MSDS for more information about safe use, physical & health hazards.

## Technical Properties

Parameter	Value	Unit	Standard
Appearance	Colourless oil		
Density	~ 0.95	g/cc	
Viscosity at 25°C	~ 1000	cSt	ASTM D 445
Flash point	< 0	°C	ASTM D 566

Limited warranty: The information & data contained in this catalogue is accurate to the best of our knowledge or is obtained from sources, tests or experience believed by us to be accurate. User is responsible for determining whether this is fit for a particular application. We make no representation of any kind & data mentioned herein is offered without any warranty. TriboCor's sole warranty is that the product will meet the specs at the time of shipment. All data is subject of change without prior notice.

V1120

**TriboCor Technologies Private Limited,**

57/3, Opp NKCA Pharmacy, Srirampura, Mysore - 570008, India.

Customer Care : 0821 2361110, +91 934 258 9006, +91 984 409 2722

E-mail : tribocor@gmail.com

Web : www.tribocor.co.in

**TriboCor**<sup>®</sup>  
*High Performance Aerosol*