# **PTFE Bonded Coating Spray TC 48**



## **Product description**

PTFE Bonded Coating Spray TC 48 is a dry film lubricant formulated to provide a long lasting PTFE reinforced durable coating on surfaces to reduce friction, wear and provide releasing properties.

## **Applications**

A white, non-toxic film provides a lubricating medium with very low frictional properties. This is also used as a dry anti-stick film and light lubrication of links, pins, chutes, slides operating in food industries.

## **Advantages**

Dry film lubricant designed to provide life time lubrication for lightly loaded or slow moving, sliding surfaces • It forms a bonded film of PTFE which reduces friction and wear. • Keeps on lubricating even after the coating is no longer visible.

#### Handling instructions.

Shake the can well before use, till the movement of steel ball inside the can is audible. Keep away from open flame & heat. Do not store above 50°C .Contents under pressure. Highly flammable material. Check for compatibility before use. Use a brush to remove hard deposits from the chain. Refer MSDS for more information about safe use, physical & health hazards.

**Technical Properties** 

Parameter	Value	Unit	Standard
Appearance	White film		
Density	~ 0.80	g/cc	
Film thickness	15	Microns	
Drying time	~10	Minutes	
Flash point	< 0	°C	ASTM D 566

Limited warranty: The information & data contained in this catalogue is accurate to the best of our knowledge or is obtained from sources, tests or experience believed by us to be accurate. User is responsible for determining whether this is fit for a particular application. We make no representation of any kind & data mentioned herein is offered without any warranty. TriboCor's sole warranty is that the product will meet the specs at the time of shipment. All data is subject of change without prior notice.

