

# Mould Release Fluid TC 52



## Product description

Mould Release Fluid TC 52 is an efficient release agent on rubber and plastic moulds. It forms very thin film, which is non-staining, non-sticky and non-toxic. It can be used as general lubricant and as anti-spatter fluid.

## Applications

Can be used as mould release agent in injection moulding, anti-spatter agent and general lubricant.

## Advantages

Odourless, tasteless & non corrosive • Very high flash point • Available in various grades • Safe on metals

## Handling instructions

Can be applied by brush or dip. Refer MSDS for more information about safe use, physical & health hazards.

## Technical Properties

Parameter	Value	Unit	Standard
Appearance	Colourless fluid		
Base	Silicone		
Density	0.95	g/cc	
Flash point	>250	°C	ASTM D 92

Limited warranty: The information & data contained in this catalogue is accurate to the best of our knowledge or is obtained from sources, tests or experience believed by us to be accurate. User is responsible for determining whether this is fit for a particular application. We make no representation of any kind & data mentioned herein is offered without any warranty. TriboCor's sole warranty is that the product will meet the specs at the time of shipment. All data is subject of change without prior notice.

V1120

**TriboCor Technologies Private Limited,**

57/3, Opp NKCA Pharmacy, Srirampura, Mysore - 570008, India.  
Customer Care : 0821 2361110, +91 934 258 9006, +91 984 409 2722  
E-mail : tribocor@gmail.com Web : www.tribocor.co.in

**TriboCor**<sup>®</sup>  
*High Performance Aerosol*