# **Adhesive Chain Fluid TC 55**



### **Product description**

Adhesive Chain Lube TC 55 is an effective adhesive chain lubricant for lubrication and corrosion protection of industrial chains, wire ropes, cables, pulleys, gear drives etc. Specially formulated to give optimum lubrication and corrosion protection to chains working under hostile conditions.

### **Applications**

TC 55 is used for superior lubrication & corrosion protection of all types of industrial chains, conveyors, wire ropes, gear drives, pulleys etc.

# **Advantages**

Highly adhesive & resistant to thrown off • Excellent corrosion & wear protection • Resistant to water • Safe on metals • Outstanding penetration & creeping properties.

#### **Handling instructions**

Can be applied by brush or dip. Refer MSDS for more information about safe use, physical & health hazards.

# **Technical Properties**

Parameter	Value	Unit	Standard	
Appearance	Brown fluid			
Viscosity	Min 200	cSt	ASTM D445	
Density	~0.90	g/cc		
Flash point	>200	°C	ASTM D 92	
Service temperature	-20 to 200	°C		·

Limited warranty: The information & data contained in this catalogue is accurate to the best of our knowledge or is obtained from sources, tests or experience believed by us to be accurate. User is responsible for determining whether this is fit for a particular application. We make no representation of any kind & data mentioned herein is offered without any warranty. TriboCor's sole warranty is that the product will meet the specs at the time of shipment. All data is subject of change without prior notice.

E-mail: tribocor@gmail.com

