

# HT Chain Fluid TC 58

## Product description

TC 58 is a high temperature lubricant which is formulated with synthetic base oils having high temperature lubricating capability. Careful selection of additives results in fluid which resists high temperature decomposition and prevents the formation of sludge etc. This result in longer equipment life, less maintenance & higher efficiency.

## Applications

Used as high temperature lubricant for roller bearings, gears of sophisticated equipment operating under high temperatures. It can also be used for tenter frame ovens, ceramics & glass productions. It is also recommended for paint curing ovens, paper and ply wood manufacturing.

## Advantages

Excellent high temperature oxidation resistance • Superior thermal stability • Extremely low volatility • Good wetting property

## Handling instructions

Can be applied by brush or dip. Refer MSDS for more information about safe use, physical & health hazards.

## Technical Properties

Parameter	Value	Unit	Standard
Appearance	Yellowish brown		
Viscosity	VG 220	cSt	ASTM D445
Density	~0.83	g/cc	
Flash point	>240	°C	ASTM D 92
Service temperature	-20 to 220		

Limited warranty: The information & data contained in this catalogue is accurate to the best of our knowledge or is obtained from sources, tests or experience believed by us to be accurate. User is responsible for determining whether this is fit for a particular application. We make no representation of any kind & data mentioned herein is offered without any warranty. TriboCor's sole warranty is that the product will meet the specs at the time of shipment. All data is subject of change without prior notice.

V1120

**TriboCor Technologies Private Limited,**

57/3, Opp NKCA Pharmacy, Srirampura, Mysore - 570008, India.  
Customer Care : 0821 2361110, +91 934 258 9006, +91 984 409 2722  
E-mail : tribocor@gmail.com Web : www.tribocor.co.in

**TriboCor**<sup>®</sup>  
High Performance Aerosol