

# Conformal Coating Fluid TC 60



## Product description

Conformal Coating Fluid TC 60 is an effective fast drying product based on acrylic for protection of all electrical and electronic components. This meets the requirement of MIL-I-46058C and ROHS specifications. TC 60 is UV reflective in nature. Operating temperature is up to 120°C.

## Applications

TC 60 is used for the protection of printed circuit boards from humidity, fungus and corrosion. The coating is transparent and coated components can easily be identified.

## Advantages

High temperature resistance • Fast drying • UV reflective • Protects against fungus & moisture

## Handling instructions

Can be applied by brush or dip. Refer MSDS for more information about safe use, physical & health hazards.

## Technical Properties

Parameter	Value	Unit	Standard
Appearance	Colourless fluid		
Density	~0.90	g/cc	
Flash point	< 5	°C	ASTM D 92
Service temperature	-20 to 120	°C	

Limited warranty: The information & data contained in this catalogue is accurate to the best of our knowledge or is obtained from sources, tests or experience believed by us to be accurate. User is responsible for determining whether this is fit for a particular application. We make no representation of any kind & data mentioned herein is offered without any warranty. TriboCor's sole warranty is that the product will meet the specs at the time of shipment. All data is subject of change without prior notice.

V1120

**TriboCor Technologies Private Limited,**

57/3, Opp NKCA Pharmacy, Srirampura, Mysore - 570008, India.  
Customer Care : 0821 2361110, +91 934 258 9006, +91 984 409 2722  
E-mail : tribocor@gmail.com      Web : www.tribocor.co.in

**TriboCor**<sup>®</sup>  
**High Performance Aerosol**