

Anti-Spatter Fluid TC 69



Product description

TC 69 has outstanding performance preventing spatter sticking to a wide range of steels, including mild steel, stainless, steels and aluminium.

Applications

Water miscible release agent and anti-spatter liquid in concentrate form used to prevent sticking of welding spatters on the job during welding.

Advantages

Water washable • Stable emulsion • Colour indicator • Suitable welding task • Usage ration 1: 4

Handling instructions

Can be applied by brush or dip. Refer MSDS for more information about safe use, physical & health hazards.

Technical Properties

Parameter	Value	Unit	Standard
Appearance	Blue fluid		
Density	~0.83	g/cc	
Flash point	➤ 200	°C	ASTM D 92
Service temperature	-20 to 120	°C	

Limited warranty: The information & data contained in this catalogue is accurate to the best of our knowledge or is obtained from sources, tests or experience believed by us to be accurate. User is responsible for determining whether this is fit for a particular application. We make no representation of any kind & data mentioned herein is offered without any warranty. TriboCor's sole warranty is that the product will meet the specs at the time of shipment. All data is subject of change without prior notice.

V1120

TriboCor Technologies Private Limited,

57/3, Opp NKCA Pharmacy, Srirampura, Mysore - 570008, India.
Customer Care : 0821 2361110, +91 934 258 9006, +91 984 409 2722
E-mail : tribocor@gmail.com Web : www.tribocor.co.in

TriboCor®
High Performance Aerosol