## **Product description**

Red Insulating Varnish Spray TC 80 is an effective fast drying product for protection of all electrical and electronic components. A tough flexible coating that protects and insulates exposed wire, components and electrical windings.

### Applications

TC 80 is used for the protection of electrical connections, switches, terminal boards, and motor windings from humidity, fungus and corrosion.

### Advantages

Enhances electrical equipment life spans, prevents failures breakdowns • High dielectric strength • Excellent oil and moisture resistance • Class B, flexible, tough, high dielectric strength arc & tracking resistant finishing electrical varnish. • Penetrates, coats, insulates & seals in one step • Excellent finish – tough, flexible, glossy, and durable red coat.

### **Handling instructions**

Shake the can well till movement of ball inside the can is audible. Keep away from open flame & heat. Do not store above 50°C .Contents under pressure. Highly flammable material. Check for compatibility before use. Refer MSDS for more information about safe use, physical & health hazards.

### **Technical Properties**

Parameter	Value	Unit	Standard
Appearance	Red dry film		
Density	~ 0.90	g/cc	
Film thickness	50	Microns	
Drying time	~ 20	Minutes	
Flash point	< 0	°C	ASTM D 566

Limited warranty: The information & data contained in this catalogue is accurate to the best of our knowledge or is obtained from sources, tests or experience believed by us to be accurate. User is responsible for determining whether this is fit for a particular application. We make no representation of any kind & data mentioned herein is offered without any warranty. TriboCor's sole warranty is that the product will meet the specs at the time of shipment. All data is subject of change without prior notice.

# TriboCor Technologies Private Limited,

57/3, Opp NKCA Pharmacy, Srirampura, Mysore - 570008, India. Customer Care : 0821 2361110, +91 934 258 9006, +91 984 409 2722 E-mail : tribocor@gmail.com Web : www.tribocor.co.in

