## **Product description**

Corrosion Protection Spray TC 81 is designed to protect the metals from corrosion in hostile conditions. It forms a dry film for the protection of tools, moulds and machines. It gives a multi metal protection.

## Applications

Corrosion Protection Spray TC 81 is used for the protection of tools, moulds and machines.

## Advantages

Quick drying type • Excellent oil and moisture resistance • Multi metal indoor protection

### Handling instructions

Shake the can well till movement of ball inside the can is audible. Keep away from open flame & heat. Do not store above 50°C .Contents under pressure. Highly flammable material. Check for compatibility before use. Refer MSDS for more information about safe use, physical & health hazards.

#### **Technical Properties**

Parameter	Value	Unit	Standard
Appearance	Light yellow film		
Туре	Dry film	g/cc	
Film thickness	`50	Microns	
Drying time	~ 15	Minutes	
Flash point	< 0	°C	ASTM D 566

Limited warranty: The information & data contained in this catalogue is accurate to the best of our knowledge or is obtained from sources, tests or experience believed by us to be accurate. User is responsible for determining whether this is fit for a particular application. We make no representation of any kind & data mentioned herein is offered without any warranty. TriboCor's sole warranty is that the product will meet the specs at the time of shipment. All data is subject of change without prior notice.

# TriboCor Technologies Private Limited,

57/3, Opp NKCA Pharmacy, Srirampura, Mysore - 570008, India. Customer Care : 0821 2361110, +91 934 258 9006, +91 984 409 2722 E-mail : tribocor@gmail.com Web : www.tribocor.co.in

